

LODGEMENT CHECKLIST (Pool/Spa & Barrier) – Building Permit (VIC)

	ONE (1) digital copy of ALL plans and documentation is required.	
	Application Form (Inc. Owners Appointment of Building Surveyor)	
	Title Search Certificate (Proof of ownership – certificate must be less than 3 months old)	
	Plan of Subdivision (For New Pools/Spas)	
	Domestic Building Insurance Certificate (If using registered building practitioner and value of work >\$16k)	
	Major Domestic Building Contract (If using registered building practitioner and value of work >\$10k)	The plan must include: • Boundaries and dimensions of the site as detailed on the
	Owner Builder Certificate of Consent (For works over \$16k) & building works cost justification (if applicable) Construction details Plans and elevations to scale (not less than 1:100) describing building materials and methods of construction Details of safety barrier showing compliance with Australian Standard 1926.1-2012 (Inc. Test Reports of all Fencing components demonstrating compliance) Soil/Site Classification Report (If available) Performance Solution Report — Required for any sewer/wastewater connection (BCA Performance Requirement P2.2.4 — Drainage from swimming pools) Details of the following proposed water recirculation compliance items (AS1926.3): (Compliance certificate) Detailed drawings of the recirculation & filtration system, showing the location of all suction points including solar suction. Demonstrate that suction points will be not less than 600mm apart. Pipe sizes Skimmer Box Outlet Covers Filtration System	Plan of Subdivision including any easements. • The location of existing buildings, decks, retaining walls and climbable structures etc. including detail of any openings (e.g. doors, windows) • The location and detail of Pool/Spa safety barriers (ie all enclosure fencing, gates, shielding, walls etc.) including the following: - 1.2m minimum height for pool/spa fence, no gaps exceedin 100mm (fence openings or bottom of fence), no climbable members as per AS1926 (2012) - 1.8m minimum height for boundary fences (include type e.g solid paling, colourbond and showing Non-climbable zone of 900 mm arc from the inside top of fence) if used as part of pool barrier - Intersecting fences with climbable rails etc to be installed with solid shielding (e.g.palings) at least a horizontal distance of 900mm (outside) & 300mm (inside) pool enclosure - No climbable objects within 900mm horizontal arc distance of safety barriers - Gates must swing outwards from pool/spa enclosure with 1.5m minimum height self latching & closing device (Unless
	- Heating & Pumping Site plan Scale (1:200), north point	shielded as per AS1926 (2012) - Dwelling, shed & outbuilding doors are not permitted to open into the pool/spa enclosure
	 ☐ Site boundary dimensions ☐ Setback dimensions ☐ Location of easements (type) ☐ Location of structures (existing and proposed) ☐ Location of fences (existing and proposed) 	 Windows with sills less than 1.8m high and no climbable objects are to be permanently restricted from opening more than 100mm width Fencing details are to demonstrate compliance with AS 1926.1 (2012) and are to detail the proposed height, spacing between timber / steel members and footing details
	** Impact Building Approvals can obtain Title & Restrictions Docs if required for an additional fee of \$66 per document. (Please advise)	

ABN: 65 447 239 743